

Audio

Inputs:	VCR-1 (rear), VCR-2 (front & rear), 3 Auxiliary, 1 Line, 1 Tape, 1 Mic
Isolation:	Better than 70dB, between inputs
Input Level:	0.5V rms
Input Impedance:	47k Ohms
Frequency Response:	20Hz - 20kHz (± 0.5dB)
S/N Ratio:	Better than 86dB
Distortion:	Without EQ, DNR, Hiss Filter, and Stereo Synthesis engaged - 0.1% With EQ, DNR, Hiss Filter, and Stereo Synthesis engaged - 0.2%
Graphic Equalizer Frequency Centers:	31.5Hz, 63Hz, 125Hz, 250Hz, 500Hz, 1kHz, 2kHz, 4kHz, 8kHz, and 16kHz
Graphic Equalizer Control Range:	± 12dB
DNR (Dynamic Noise Reduction):	- 10dB
Hiss Filter:	- 6dB at 10kHz
Outputs:	1 Monitor, 3 VCR (stereo), 1 Tape
Output Level:	0.5V rms
Output Impedance:	1k Ohms

Video

Color System:	3.58MHz color subcarrier (NTSC)
Inputs:	VCR-1 (rear), VCR-2 (front & rear), 3 Auxiliary
Input Level:	1.0V p-p
Input Impedance:	75 Ohms
Frequency Response:	± 3dB to 5MHz
S/N Ratio:	67dB
Sharpness Enhance Level:	4dB minimum (referenced 1.0V p-p)
Detail Enhance Level:	6dB minimum (referenced 1.0V p-p)
Outputs:	1 Monitor, 3 VCR
Output Level:	1.0V p-p
Output Impedance:	75 Ohms

RF Modulator

Inputs:	VHF Antenna, Video, & Audio (internal connected)
Output:	VHF Antenna (through) or Video & Audio (modulated)
Output Channel:	3 or 4 switchable
Output Impedance:	75 Ohms unbalanced

General

Power Requirements:	220V 115V AC, 50/60Hz, 20W
Weight:	10 lbs
Dimensions:	19" wide x 5-3/8" high x 8-13/16" deep